



P/N:4021
10-18-100

HIGH PERFORMANCE LITHIUM CELL


SIZE
AAA

- + Low Rate Capability
- + Lithium / Thionyl Chloride Chemistry
- + Custom terminations available

CELL SPECIFICATIONS

Open Circuit Voltage (25° C)	3.65 V
Rated Discharge Current	2.0 mA
Rated Capacity	0.35 Ah
Max Current to Achieve 100% Capacity	2.0 mA
Cell Diameter (nominal)	9.5 mm (0.37 in.)
Cell Length (nominal)	18.0 mm (0.71 in.)
Cell Weight	3.9g
Lithium Weight	0.1g
Self Discharge	2% per year at 25°C
Operating Temperature	-40°C to +100°C -40°F to +212°F


OPERATING TEMPERATURE




Rev: Jan 2006

PROPRIETARY AND CONFIDENTIAL: Proprietary information is contained herein. It is not to be used, reproduced or disclosed to others without prior written consent by GREATBATCH LTD.

25°C Discharge



Capacity as a function of current and temperature



+ 9645 WEHRLE DRIVE, CLARENCE, NEW YORK 14031
 + 716.759.5800 TEL + 716.759.2562 FAX + WWW.ELECTROCHEMPOWER.COM
 + SALES@ELECTROCHEMPOWER.COM + A DIVISION OF GREATBATCH LTD.

