



+

P/N:4362  
33-60-150MR

# HIGH PERFORMANCE LITHIUM CELL

SIZE  
D

- + Moderate Rate Capability
- + Lithium / Thionyl Chloride Chemistry
- + Custom terminations available

## CELL SPECIFICATIONS

Open Circuit Voltage (25° C)	3.67 V
Rated Discharge Current	100 mA
Rated Capacity	10.0 Ah
Max Current to Achieve 100% Capacity	170 mA
Cell Diameter (nominal)	31.75 mm (1.25 in.)
Cell Length (nominal)	57.94 mm (2.28 in.)
Cell Weight	105g
Lithium Weight	3.7g
Self Discharge	2% per year at 25°C
Operating Temperature	-40°C to +150°C -40°F to +302°F


## OPERATING TEMPERATURE




Rev: Jan 2006

PROPRIETARY AND CONFIDENTIAL: Proprietary information is contained herein. It is not to be used, reproduced or disclosed to others without prior written consent by GREATBATCH LTD.

150°C discharge



Capacity as a function of current and temperature



+ 9645 WEHRLE DRIVE, CLARENCE, NEW YORK 14031  
 + 716.759.5800 TEL + 716.759.2562 FAX + WWW.ELECTROCHEMPOWER.COM  
 + SALES@ELECTROCHEMPOWER.COM + A DIVISION OF GREATBATCH LTD.



THE WORLD'S MOST RELIABLE > MOST DURABLE > LONGEST-LASTING > CELLS AND BATTERY PACKS