



**P/N:3B36  
CSC93**

# HIGH PERFORMANCE LITHIUM CELL

**SIZE  
DD**

- + High Rate Capability
- + Lithium / Sulfuryl Chloride Chemistry
- + Custom terminations available

## CELL SPECIFICATIONS

|                              |                                  |
|------------------------------|----------------------------------|
| Open Circuit Voltage (25° C) | 3.9 V                            |
| Rated Discharge Current      | 1.0 A                            |
| Rated Capacity               | 30 Ah                            |
| Maximum Continuous Current   | 4.0 A                            |
| Cell Diameter                | 33.5 mm (1.32 in.)               |
| Cell Length                  | 111.4 mm (4.39 in.)              |
| Cell Weight                  | 213g                             |
| Lithium Weight               | 10.2g                            |
| Safety Fuse                  | 7.0 A                            |
| Self Discharge               | 3% per year at 25°C              |
| Operating Temperature        | -20°C to +93°C<br>-4°F to +200°F |


## OPERATING TEMPERATURE




PROPRIETARY AND CONFIDENTIAL: Proprietary information is contained herein. It is not to be used, reproduced or disclosed to others without prior written consent by GREATBATCH LTD.

Rev: Jan 2006

25°C discharge



Capacity as a function of current and temperature



+ 9645 WEHRLE DRIVE, CLARENCE, NEW YORK 14031  
 + 716.759.5800 TEL + 716.759.2562 FAX + WWW.ELECTROCHEMPOWER.COM  
 + SALES@ELECTROCHEMPOWER.COM + A DIVISION OF GREATBATCH LTD.



THE WORLD'S MOST RELIABLE > MOST DURABLE > LONGEST-LASTING > CELLS AND BATTERY PACKS