# 3B1065


## High Rate AA Cell Lithium Sulfuryl Chloride

#### PMX150 Series

## Physical Characteristics

Chemistry	Sulfuryl Chloride
Construction	Spiral
Cell Size	AA
Length <sup>1</sup>	53.1 mm
Diameter <sup>2</sup>	13.7 mm
Cell Weight	17.0 g
Lithium Weight	0.3 g
Integrated Safety Fuse	Yes


Cell Drawing



#### Electrical Characteristics

Cell Type	Primary
Open Circuit Voltage (25°C)	3.93 V
Nominal Capacity	1.7 Ah
Maximum Continuous Current	150 mA
Operating Temperature	-20°C to +150°C
Self Discharge Rate	<3% per year
Storage Temperature	≤ 25°C
Discharge Condition	20 mA, 120°C

Discharge Curve 20 mA, 120°C



### **Key Features**

- Primary chemistry (non-rechargeable)
- High rate capability
- Advanced spiral-wound technology
- Stainless steel container
- Hermetic glass-to-metal sealing
- Restricted for transportation (Class 9)
- Custom terminations available

## Main Applications<sup>3</sup>

- Military communications
- Oceanographic buoys and gliders
- Tracking systems
- Sensor systems
- Pipeline inspection gauges
- Beacons, transponders and receivers
- Seismic surveying birds

NOTE: <sup>1</sup> The information on this datasheet is for marketing purposes only. Please consult with Electrochem for more information regarding how our cells will perform within your application. <sup>2</sup> The information in this document is subject to change without notice and does not constitute a warranty of performance. <sup>3</sup> This product and its external electrical contact materials are RoHS compliant. See our "RoHS Statement" for more information. <sup>4</sup> The length dimension was based off of a flat termination. The use of other terminations will impact overall cell length. <sup>5</sup> Diameter measurements include shrink when application needs.